



Product rating

- A Stock item generically marked
- B Locally marked in house.
- C Factory manufactured and marked
- D Price and delivery on application (long lead item)

Applications:

Containers	Cabinet/doors/hatches
Trailers	In-bond shipments
Rail cars	Control cabinets

Features:

Approved by the sweetener industry for bulk rail & truck shipments Features non-preformed security cable that frays when cut

Specifications

Made of non-performed, galvanised aircraft control cable Cable diameter measures 1/16" (1.5 mm); 12" (30 cm) long, custom lengths available Optional 3/32" (2.5mm) cable diameter (D) Corrosion-resistant lock body (zinc) Tensile strength: 750 lbf. (3.3 kN) Removal: cable cutters

Product ratings options:

- A Cold stamped TBE & numbered
- B Black anodised & lasered in house.
- C Cold stamped or Powder coated and lasered at factory.
- D Powder coated & ink jet also non ferrous versions.

Tracking identification

Additional marking options available with two lines of up to 8 characters and 6 digits. Laser Tag Serial Number Transfer optional.

Decoration/Printing options:

Mill finish. Cold stamp. Laser marking Cold stamped marking with two lines of up to 6 characters and 6 digits Ink Jet

Colours:

Red, blue, green, yellow, black, white, orange. (C & D)

US Patent

5,352,003

Product numbers CEZ116, CEZ332

Packaging

500 per box; 30 lbs. per box, 13 kg, .0205 m3, .72 ft3. Box dimensions: 16"x13"x6" (41cm x 33 cm x 16cm)


Product Sheet

1/16" EZ Loc - Cable security seal

EZ Loc is a medium-duty cargo security seals featuring non-preformed security cable that frays when cut with various marking options for customized tracking. EZ Loc comes in two sizes 1/16" which is approved by the sweetener industry for bulk rail & truck shipments and 3/32" which is preferred by the chemical & food processing industries.







Tyden Brammall of Scandinavia Fragtsikkerhedseksperten Stolpegårdsvej 7 DK 2820 Gentofte +45 39 68 26 34 / +45 24 21 34 40 www.tyden.dk / www.fragtsikkerhedseksperten.dk / www.forsegling.eu "Når de ikke kan brydes, kan der ikke snydes"